

XP STANDARD SPECIFICATIONS

XP55 55,000 lbs. rating in 4 ft.** 65,000 lbs. rating in 10 ft.**

XP65 65,000 lbs. rating in 4 ft.** 75,000 lbs. rating in 10 ft.**

XP75 75,000 lbs. rating in 4 ft.** 85,000 lbs. rating in 10 ft.**

Length 45ft, 48ft, 53ft

Main Beam 2-piece extruded and welded

Neck Transition 8", 11", 13" deep

Floor Patented 12" decking with 2 nailers + "CRT" Crush Resistant Technology™ + Multi-position J-Track (up to 5 locations)

Crossmembers C Style 14" and 18" on center + coil pack options for concentrated loads

Side Rail J-Track, with spools pockets and rub rail

Suspension MTM23T Meritor/ with AxlePak5 (5-year wheel end warranty)***

Kingpin 18"-36"

Brake System Wabco iABS

Landing Gear Jost AX150 (10 year warranty)

Electrical/Lights Grote ULTRA-BLUE-SEAL harness + 5 markers (including mid-turn marker combo) + rear lights 3-STT, 3-ICC markers, 3-STT

Tires RoadX RH652 (available in 22.5 or 24.5) Bridgestone (available in 22.5 or 24.5)

Additional Features Removable front and rear access panels, Bolt on bumper, Patent pending interior cross frame members, Air and electric lines; separated for ease of maintenance, Winch track, road side or road and curb side, Winches and straps, 4-post enclosed bolt on rear bumper, Auxiliary power cords with 7-way ISO plug or 4 pin plug, Lift axle with manual and/or electric controls, Dual air and electric (front and between landing gear)

Warranty 5-year limited (all purchased components are covered by original manufacture)

** Capacity based on 48 ft. length with 24" king pin setting and 122" suspension spacing. Capacities will change by changing configuration.

*** Disc brakes available