

XS STANDARD SPECIFICATIONS

XS60 50,000 lbs. rating in 4 ft.** 60,000 lbs. rating in 10 ft.**

XS70 60,000 lbs. rating in 4 ft.** 70,000 lbs. rating in 10 ft.**

Length 48ft, 51ft, 53ft

Main Beam 2-piece extruded and welded

Deck Height 40"- 41" (22.5 tires), 37"- 38" (19.5 tires), 34"- 35" (17.5 tires)

Neck Transition 11" and 13" deep

Floor Patented 12" decking with 2 nailers + "CRT" Crush Resistant Technology™ + Multi-position J-Track (up to 5 locations)

Crossmembers C Style 12" and 18" on center + mid-coil pack for concentrated loads

Side Rail J-Track, with spools pockets and rub rail

Suspension MTM23L Meritor/ with AxlePak5 (5-year wheel end warranty) CXU23k/ with HXL5 (required with 17.5 tires & wheels) (5-year wheel end warranty)

Brake System Wabco iABS

Landing Gear Jost AX150 (10 year warranty)

Electrical/Lights Grote ULTRA-BLUE-SEAL harness + 5 markers (including mid-turn marker combo) + rear lights 3-STT, 3-ICC markers, 3-STT

Tires RoadX RH652 (available in 22.5, 19.5, and 17.5 options)
Bridgestone (available in 22.5, 19.5, and 17.5 options)

Additional Features Removable front and rear access panels, Bolt on bumper, Patent pending interior cross frame members, Air and electric lines; separated for ease of maintenance, Winch track, road side or road and curb side, Winches and straps, 4-post enclosed bolt on rear bumper, Auxiliary power cords with 7-way ISO plug or 4 pin plug, Lift axle with manual and/or electric controls, Dual air and electric (front and between landing gear)

Warranty 5-year limited (all purchased components are covered by original manufacture)

** Capacity based on 48 ft. length with 24" king pin setting and 122" suspension spacing. Capacities will change by changing configuration.

*** Disc brakes available

**** Coupler plate available in 5/16" or 3/8" galvanized steel